

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A container with a comb for applying a substance, the container with a comb comprising:

a laminated container body having a neck portion, and including an outer layer and an inner layer delaminatable ~~therefrom~~ from the outer layer;

a hollow comb having a shaft and one or ~~plurality of~~ more discharge orifice(s); and orifices;

a cap-like ~~cap~~ member which is formed at a lower end of the shaft and fitted on the neck portion of the laminated container body, such that a liquid in the laminated container body is discharged from the ~~discharge orifice(s)~~ one or more discharge orifices through the shaft, wherein the ~~cap-like member (21)~~ cap member is formed as a separate body from the ~~shaft (32); shaft, and that~~

a pump cylinder (11) is depending ~~pump cylinder~~ extending from the cap-like member (21) ~~cap member~~ into the laminated container body (1) ~~body~~, and

a stem (41) is depending ~~a stem~~ extending from the shaft (32) ~~shaft~~ into the pump cylinder (11); pump cylinder, and having the stem having a lower end portion to which a ~~eylindrical piston (44)~~ cyllindrical piston is provided, the ~~stem (41)~~ stem and the ~~eylindrieal piston (44)~~ cyllindrical piston being biased upwardly and being vertically movably movable with respect to the laminated container body and the cap member by means of the comb (31) ~~with the shaft with respect to the laminated container body (1) and the cap-like member (21).~~

2. (Currently Amended) A container with a comb for applying a substance, the container with a comb comprising:

a double container body consisting of comprising:

an outer container and container;

an inner container which is shrinkable upon depressurization, and having depressurization; and

a neck portion;

a hollow comb having a shaft and one or plurality of more discharge orifice(s); and orifices;

a cap-like member which a cap member that is formed at a lower end of the shaft and fitted on the neck portion, such neck portion such that a liquid in the inner container is discharged from the discharge orifice(s) through the shaft orifices,

wherein the cap-like member (21) cap member is formed as a separate body from the shaft (32), shaft, and that

a pump cylinder (11) is depending a pump cylinder extending from the cap-like member (21) cap member into the inner container (11) inner container, and

a stem (41) is depending stem extending from the shaft (32) shaft into the pump cylinder (11) and pump cylinder, the stem having a lower end portion to which a eylindreal piston (44) cylindrical piston is provided, the stem (41) stem and the eylindreal piston (44) cylindrical piston being biased upwardly and vertically movably-movable with respect to the double container body and the cap member by means of the comb (31) with the shaft with respect to the double container body (10) and the cap-like member (21).

3. (Currently Amended) A container with a comb for applying substance according to the according to claim 1, echaracterized in that further comprising a depression

~~rod (34) is a depression rod protruding laterally outwardly from a lower portion of the shaft~~
~~(32) shaft.~~

4. (Currently Amended) A container with a comb for applying substance
~~according to the~~ according to claim 1, characterized in that further comprising a stop cylinder
~~(51) for preventing a stop cylinder that prevents an escape of the cylindrical piston (44)~~
is cylindrical piston, the stop cylinder being fixed to an upper end portion of the pump
~~cylinder (11) pump cylinder and being inserted into an upper part of the pump cylinder.~~

5. (Currently Amended) A container with a comb for applying a substance
~~according to the~~ according to claim 1, characterized in that the cap-like member (21) further
comprising a cap member having a peripheral wall (23) wall, a lower half of which the
peripheral wall is fitted on the neck portion (5) neck portion of the laminated container body
~~(4) body or on the double container body (10) body, and an inward flange-like wall~~
~~(25), (27) flange protruding from an intermediate portion of the peripheral wall (23) peripheral~~
wall, an inner circumference of the inward flange-like wall flange is continuously connected to
the pump cylinder (11) pump cylinder, and also in that a lower end portion of the shaft (32) is
radially expanded shaft that expands radially outward to define an expanded cylinder (73)
~~which is expanded cylinder that is fitted vertically slidably within an upper half of the~~
peripheral wall (23) peripheral wall, a shoulder portion (72) a shoulder portion for depression
~~is depressing that is formed between the expanded cylinder (73) expanded cylinder and the~~
~~other part of the shaft (32) other portions of the shaft excluding its lower portion, and the stem~~
~~(41) the stem is provided at its upper end portion with an outer flange (46) outer flange for~~
~~fitted to an inner surface of the expanded cylinder (73) expanded cylinder, and also in that a~~
~~spring (48) a spring for upwardly biasing the outer flange (46) outer flange, the spring being is~~
~~provided between the outer flange and the inner flange-like wall (25), (27) inward flange.~~

6. (Currently Amended) A container with a comb for applying substance according to the claim 1, ~~characterized in that the outer layer (1A) of the laminated container body (1) is a shape retentive, stiff layer wherein the outer layer of the laminated body has a~~ retentive shape.

7. (Currently Amended) A container with a comb for applying a substance according to the claim 2, ~~characterized in that the outer container (8) is excellent in shape retentivity wherein the outer layer of the outer container has a retentive shape~~.